

# XT512

**SCHONSTEDT**   
INSTRUMENT COMPANY  
*Making Locating Easier Since 1953*  
100% EMPLOYEE-OWNED COMPANY

## Optimized for Sonde and Camera Locating

- ✓ Water & Sewer
- ✓ Construction & Excavation



World of SCHONSTEDT



WORLD OF LOCATING

[schonstedt.com](http://schonstedt.com)



**SCHONSTEDT**  
MADE IN USA



## Receiver Specifications

Operating Frequency:	512 Hz plus 50/60 Hz passive detection
Battery:	One 9V Alkaline Battery
Battery Life:	18 Hours (intermittent use)
LCD Display:	3.5" Digit Reflective Signal Strength, Directional Arrows, Battery Status, Volume and Depth on Sonde/Camera and Passive
Controls:	ON/VOLUME ADJUSTMENT OFF DEPTH SONDE AUTO GAIN UP GAIN DOWN GAIN PASSIVE
Dimensions:	Unit extended: 27.7 in (~70 cm) Unit collapsed: 17.5 in (~44 cm)
Weight:	Under 2.5 lbs
Operating Temperature	-4°F to 140°F (-20°C to 70°C)
Dust & Water Protection	Rated IP54, when operated with earphone jack plug (provided)



Contact Us:  
**800-999-8280**  
**info@schonstedt.com**

Find Your Local Dealer:  
**schonstedt.com**



**SCHONSTEDT**   
INSTRUMENT COMPANY

*Making Locating Easier Since 1953*

*an employee-owned company*